



# DUO-SAFETY LADDER CORPORATION

## Solid Beam Aluminum Ladders

These incorporate Duo-Safety's exclusive tongue and groove arrangement. This outstanding construction design holds the sections firmly and rigidly, without brackets, hooks or obstructions of any kind. These compact ladders require a minimum of banking space - and have the extra advantage of being especially stable and rigid.

### Series 900-A Series 925-A

3 1/4" Channel Rail  
750 lb Duty Rated

#### SPECIFICATIONS

SERIES 900-A 2-SECTION				
Size	Closed Length	Width	Banking Thickness	Weight
20'	12' 2.75"	21.75"	5.375"	60#
24'	14' 2.75"	21.75"	5.375"	72#
SERIES 925-A 3-SECTION				
Size	Closed Length	Width	Banking Thickness	Weight
22'	10' 8.75"	24"	7.625"	82#
26'	11' 8.75"	24"	7.625"	92#

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

**Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.**

Prong feet as Standard

Rubber safety shoes optional for hard surface use.



Model 900A



Model 925A