



DUO-SAFETY LADDER CORPORATION

Aluminum Roof Ladders

Famous Duo-Safety Rail Construction provides the advantage of extra strength without cumbersome weight. Ideal for pumper use - these outstanding ladders have been proven and approved for many years by fire companies everywhere. Installed with standard 3/4" hooks or heavy duty 7/8" hooks for an additional fee.

Series 775-A Series 875-A Series 1275-A

Channel Rail Construction
750 lb Duty Rated



SPECIFICATIONS

SERIES 775-A ROOF

| Size | Length | Width | Rail Size | Weight |
|------|-----------|-------|-----------|--------|
| 10' | 10' 2.25" | 19" | 2.75" | 22# |
| 12' | 12' 2.25" | 19" | 2.75" | 24# |
| 14' | 14' 2.25" | 19" | 2.75" | 28# |

SERIES 875-A ROOF

| Size | Length | Width | Rail Size | Weight |
|------|----------|-------|-----------|--------|
| 16' | 16' 2.5" | 19" | 3.25" | 39# |
| 18' | 18' 2.5" | 19" | 3.25" | 44# |
| 20' | 20' 2.5" | 19" | 3.25" | 48# |

SERIES 1275-A ROOF

| Size | Length | Width | Rail Size | Weight |
|------|--------|-------|-----------|--------|
| 25' | 25' 3" | 19" | 3.75" | 64# |
| 30' | 30' 3" | 19" | 3.75" | 72# |

All dimensions listed are N.F.P.A. Design Verification Standards. Variations occur in each product of approximately +/- .125" due to the type of rivets, nuts, bolts etc. used. If you require precise dimensions, please call our office and request a copy of our current field dimension sheets.

Weight listed is actual weight of product only. For shipping purposes, please call our office for packaged weight before obtaining freight estimates.

Prong feet as Standard

Rubber safety shoes optional for hard surface use.

DUO-SAFETY LADDER CORPORATION 513 W 9th Avenue PO Box 497 Oshkosh WI 54903-0497

Toll Free: 877-386-5377

Fax 920-231-2460

mail@duosafety.com

www.duosafety.com