



Case Material: High-impact ABS thermoplastic housing with rubberized cushioned-grip handle

Dimensions/Weight: Length: 7.50 in. (19.05 cm) Width: 5 in. (12.7 cm) Height: 6.50 in. (16.51 cm) 1.85 lbs (839 grams) with battery ~ it floats!

Light Source: C4® LED technology, impervious to shock with a 50,000 hour lifetime. Two ultra bright blue LEDs ensure you can be seen even from behind

Light Output/ Run Time: High: 100,000 candela peak beam intensity; 180 lumens
Low: 45,000 candela peak beam intensity; 80 lumens

Deep-dish parabolic reflector produces a tight beam with optimum peripheral illumination to aid in navigation.
Optimized electronics provide regulated intensity

Run times:

- Steady High LED & tail lights: Runs 4.25 hours
- Steady Low LED & tail lights: Runs 10 hours
- Steady High LED only: Runs 5 hours
- Blinking High LED only: Runs 7 hours
- Blinking tail lights only: Runs 60 hours

Battery: Two lightweight Lithium-Ion nanotechnology cells. Recharges in 5 hrs.

On/Off/Mode Selection Push and hold momentary toggle switch to access 8 Modes of operation.

Left Modes:

- (Optional Programmable 2, 3 or 4)
- 1-Steady High LED/Steady tail lights
 - 2-Steady Low LED/Steady tail lights
 - 3-Steady High LED/No tail lights
 - 4-No LED/Steady tail lights

Right Modes:

- (Optional Programmable 2, 3 or 4)
- 1-Steady High LED/Blinking tail lights
 - 2-Steady Low LED/Blinking tail lights
 - 3-Blinking High LED/No tail lights
 - 4-No LED/Blinking tail lights

Models: Standard System - Includes quick release buckle strap, charging rack and both AC and DC chargers.

Vehicle Mount System - Includes quick release buckle strap and 12V DC vehicle-mountable direct wire charging rack.

Features: IPX7 Rated design (1 meter for 30 minutes).
Ultra lightweight at 1.85 lbs. Lantern floats.
Serialized for positive identification.

Approvals: USTC Class I, Div. 2, Grps. A,B,C,D; Class II, Div. 2, Grps. F,G; Class III T-Code: T4
Most models meet applicable European Community Directives.
Rack meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position.

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction

| Item | UPC | Item # |
|--|----------------|--------|
| Fire Vulcan LED Standard System IEC Type A (120V) AC/ 12V DC. Orange | 080926-44450-8 | 44450 |
| Fire Vulcan LED Standard System IEC Type C (230V) AC/ 12V DC. Orange | 080926-44452-2 | 44452 |
| Fire Vulcan LED Standard System IEC Type G (240V) AC/ 12V DC. Orange | 080926-44453-9 | 44453 |
| Fire Vulcan LED Standard System IEC Type A (100V) AC/ 12V DC. Orange | 080926-44455-3 | 44455 |
| Fire Vulcan LED Vehicle Mount System 12V DC - Orange | 080926-44451-5 | 44451 |
| Fire Vulcan (WITHOUT CHARGER) - Orange | 080926-44454-6 | 44454 |
| <i>See reverse side for additional part numbers</i> | | |



22060



22061



22062



#22051



#22050



#44610



#44103 Standard System Charge Rack

#44132 Direct Wire DC Charge Rack



#44050

| Item | | UPC | Part # |
|---------------------------------------|-------|----------------|--------|
| DC2 direct wire charge cord | | 080926-22050-8 | 22050 |
| DC1 Charge Cord | | 080926-22051-5 | 22051 |
| IEC Type C (230V) AC charge cord | | 080926-22061-4 | 22061 |
| IEC Type A (100V/120V) AC charge cord | | 080926-22060-7 | 22060 |
| IEC Type G (240V) AC charge cord | | 080926-22062-1 | 22062 |
| Battery - Li-ion | | 080926-44610-6 | 44610 |
| Standard System Mounting Rack | Black | 080926-44103-3 | 44103 |
| Direct Wire 12V DC Mounting Rack* | Black | 080926-44132-3 | 44132 |
| Quick Release Strap | | 080926-44050-0 | 44050 |

*Not shown