



- Material/Lens** Impact and chemical resistant Engineering Polymer resin; o-ring sealed and vented. Available in orange. Unbreakable polycarbonate lens with scratch resistant coating.
- Dims/Weight** Length: 7.00 in. (17.78 cm); Body thickness: 1.05 in. (2.67 cm); Width: 1.50 in. (3.81 cm); Face cap diameter: 1.93 in. (4.90 cm)  
6.6 oz (187 grams) with batteries (included with purchase)
- Light Source/ Output** Seven 5mm ultra-bright white LEDs, impervious to shock with a 100,000 hour lifetime.  
57 lumens; 500 candela; 45 meter beam distance; runs 24 hours
- Switch** Push-button tail switch. Sealed switch design protects it from corrosion caused by battery leakage
- Battery** 3 "AA" alkaline batteries reduce battery and recycling costs by 25%  
• Combination of visual and mechanical polarity protection ensures correct installation of batteries  
• Light designed to not power on if batteries are installed incorrectly
- Features**
- High-performance, anti-static, thermoplastic material resistant to chemicals and solvents
  - Captured locking" set screw will not back out - prevents FOD (Foreign Object Debris)
  - Safety measure: Set screw helps to avoid batteries being changed out, or the housing inadvertently being opened in a hazardous environment
  - Set screw goes into a metal tray that evenly distributes pressure to protect the body from over-tightening of the set screw
  - One body electronic LED module mechanically attached to electronic assembly
  - IP67 rated; dust-tight, waterproof to 1m for 30 minutes
  - 3 meter impact resistance tested
- Approvals**
- ATEX:**  
ATEX-approved for Category 1 (Zone 0) locations  
II 1G Ex ia IIC T4  
11 1D Ex ia IIIC To 118C Da  
DEMKO 13 ATEX 1214468X
- IECEX**  
Ex ia IIC T4 Ga  
Ex ia IIIC To 118 degrees-C Da  
IECEX UL 14.0032X
- C-UL-US Classified Class I, Division 1, Groups A, B, C, D; Class II, Division 1, Groups E, F, G; Class III; Exia; T-Class: T4  
Most models meet applicable European Community Directives.
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit [streamlight.com](http://streamlight.com) for full warranty information.

| Item   | UPC            | Part # |
|--|----------------|--------|
| 3AA ProPolymer HAZ-LO 7 LED with alkaline batteries - Blister - Orange | 080926-68772-1 | 68772  |



Hard hat and flashlight not included

Adheres to side of hard hat



68089  
Poly Mount Kit - universal mounting via slot attachment  
or self-adhesive mount

Includes adapters for mounting:  
4AA ProPolymax®  
3AA ProPolymer® HAZ-LO®  
2AA ProPolymer® Series or the PolyTac® LED Series



Clips onto hard hats



68086



68085



99075  
Helmet Strap  
Hard hat and flashlight not included



68088



85905

| Item                                       | UPC            | Part # |
|--|----------------|--------|
| 4AA/3AA helmet mount                       | 080926-68085-2 | 68085  |
| 4AA/3AA Gallet mount                       | 080926-68086-9 | 68086  |
| Nylon Holster                              | 080926-68905-3 | 68905  |
| Polymount Kit                              | 080926-68089-0 | 68089  |
| Rubber Helmet Band                         | 080926-99075-3 | 99075  |
| 3AA/4AA ProPolymer Series Belt Clip        | 080926-68088-3 | 68088  |
| Lanyard with Push Button Slide (not shown) | 080926-72024-4 | 72024  |