

Low Level Strainers



FULL FLOW CAPACITY

8" Tubing

LL602 Big Water

Base pan designed with side walls to protect the tank

- With standard external screen
- Jet Siphon, Optional



IN USE

Hose attached

STATIONARY (not in use)

NO hose attached

| Part Number | Weight (lbs.) | Length (Inches) | Height (Inches) | Width (Inches) |
|---|---------------|-----------------|-----------------|----------------|
| BIG WATER Low-Level Strainer | | | | |
| LL602* | 18.75 | 15.75 | 15 | 15.75 |
| *Recommended for pumps 1500 to 2,000 GPM | | | | |
| LL60 ** | 15 | 18 | 13.37 | 15.75 |
| **Recommended for pumps 1250 to 1500 GPM | | | | |
| LL50 | 15 | 17.4 | 12.7 | 15.75 |
| LL45 | 13 | 17.4 | 12.7 | 15.75 |
| LL40 | 12 | 17.4 | 12.4 | 15.75 |
| LL30*** | 10 | 17.25 | 10.5 | 15.75 |
| LL25*** | 10 | 17.25 | 10.1 | 15.75 |
| ***Without Jet Siphon Jet Siphon not available | | | | |

- Barrels change according to the size/flow
- Available with Foot Valve

FEATURES:

- Made with 8" tubing
- Lightweight aluminum alloy
- Water Transfer Device
- Drafts down to 2" from bottom
- Pivoting adjustable elbow
- Base pan design has additional side walls eliminating tank damage
- 2 1/2" to 6", internal screen is standard 6" Big Water; external screen standard
- Meets NFPA Standard